


	SPECIFICATIONS				
	CONTACT CARRIER MATERIAL/PLATING (P1)	ZINC/NICKEL			
	MOLDED MATERIAL/COLOR (P1)	TPU/BLACK			
	CONTACT MATERIAL/PLATING (P1)	BRASS/GOLD			
	COUPLING NUT MATERIAL/PLATING (P1)	BRASS/NICKEL			
	CONTACT CARRIER MATERIAL (P2)	POLYCARBONATE			
	MOLDED HEAD MATERIAL/COLOR (P2)	TPU/BLACK			
	CONTACT MATERIAL/PLATING (P2)	BRONZE/GOLD			
	RATED CURRENT [A]	0.5 A			
	RATED VOLTAGE [V]	42 V			
	OUTER CABLE JACKET MATERIAL/COLOR	TPO/MINT GREEN (LSZH)			
	CONDUCTOR INSULATION MATERIAL	HDPE			
	NUMBER OF CONDUCTORS [AWG]	4STPx26 AWG, STRANDED			
	SHIELDING	ALUMPOLYESTER FOIL & T-C BRAIDED			
	TRANSMISSION CHARACTERISTICS	CAT 6A			
	TEMPERATURE RANGE	-20°C to +70°C (-4°F to +158°F)			
	PROTECTION CLASS	MEETS IEC IP67 (IEC IP20:P2)			



CABLE LENGTH	TOLERANCE *				
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER				
STRIP LENGTH	TOLERANCE *				
0-7mm	±0.5mm				
8-29mm	±1.0mm ±2.0mm ±3.0mm ±4.0mm ±5.0mm				
30-49mm					
50-69mm					
70-100mm					
OVER 100mm					
* UNLESS OTHERWISE SPECIFIED					

## NOTES:

REV DESCRIPTION

H UPDATE MOLDED BODY MATERIAL

1. "\*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

		1								
		1		RELATED DOCUMENTS	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE			3000 CAMPUS MINNEAPOLIS, MI	
				1. 2. 3. 4.	<b>⊕ □</b>	PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		IRCK	1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us	
TURC		K TO ORDER	MATERIAL		DRFT RDS	DATE 06/05/12	DESCRIPTION  RSSX RJ45S 862-*M			
•	TOKEK TO OKBEK				ALL DIMENSIONS DISPLAYED ON THIS	APVD L.S.	SCALE 1=1.0	1/33/ 1/04/33	002 — NVI	
			DRAWING ARE FOR REFERENCE ONLY	UNIT OF MEASUREMENT		IDENTIFICATION NO.		REV		
				FINISH	CONTACT TURCK	MILLIMETER [ INCH ]		IDENTIFICATION NO.		1.1
	RDS	06/26/19	500000000177		FOR MORE INFORMATION	IVALE IVAL I ET ( INCOTT)			H	
╗	BY	DATE	ECO NO.			DO NOT SCALE	THIS DRAWING	FILE: 777028714	SHEET	1 OF 1

## SOURCE DRAWING - FOR REFERENCE ONLY