


DWE-1000-110-10-2B1000-H1181

Draw-Wire





Technical data

Type	DWE-1000-110-10-2B1000-H1181
ID	100049352
Measuring principle	Optical
General data	
Measuring range	1000 mm
Linearity deviation	≤ 0.05 %
Output type	Incremental
Electrical data	
Operating voltage U _B	10...30 VDC
No-load current	≤ 100 mA
Output current	≤ 30 mA
Short-circuit protection	yes
Pulse frequency max.	300 kHz
Signal level high	min. U _B - 1 V
Signal level low	max. 0.5 V
Output function	8-wire, Push-Pull/HTL, invertable
Mechanical data	
Design	Draw Wire
Housing material	Titanium anodized aluminium
Encoder housing material	Die-cast zinc
min. extension force	4.2 N
max.extension force	5.4 N
max. extension speed	10 m/s
Pull acceleration max.	140 m/s ²
wire material	Stainless steel
Electrical connection	Connector, M12 × 1

Features

- Highly dynamic draw-wire sensor
- With permanently installed incremental encoder
- Measuring principle: optical
- Sensor protection class IP65
- -20...+85 °C
- 10...30 VDC
- Push-pull/HTL with inversion
- Pulse frequency max. 300 kHz
- M12 × 1 connector, 8-pin
- 5 pulses per mm
- Resolution 0.2 mm

Wiring diagram



Technical data

Environmental conditions	
Ambient temperature	-20...+85 °C
Protection class	IP65

Accessories

RDR-1	1544753
-------	---------

Deflection roller for aluminium draw-wire sensors

