


Photoelectric Sensor Color Mark Sensor With Switching Output R58ACG1D



	58,9 40 28 80,1 39 30	
Туре	R58ACG1D	
ID	3010233	

■ C	able.	PVC.	2 m,	4-wire
-----	-------	------	------	--------

- Protection class IP67
- Threshold adjusted via 15-turn potentiome-
- Light/dark operate adjusted via rotary switch
- Emits green light for detection
- Parallel scan field relative to the housing
- Optics rotatable by 90°
- Operating voltage: 10...30 VDC
- PNP/NPN switching output
- Switching behavior adjustable (NO/NC)
- Switch-off delay 20 ms


Туре	R58ACG1D
ID	3010233
Optical data	

Optical data	
Function Inspection sensor	
Operating mode	Contrast sensor
Light type	Green
Focal distance	10 mm

1030 VDC	
< 10 % U _{ss}	
≤ 100 mA	
≤ 75 mA	
yes	
yes	
NO contact, PNP/NPN	
10 kHz	
≤ 100 ms	
Potentiometer	
	< 10 % U _{ss} ≤ 100 mA ≤ 75 mA yes yes NO contact, PNP/NPN 10 kHz ≤ 100 ms


Setting option	Potentiometer	
Mechanical data		
Design	Rectangular, R58	
Housing material	Metal, Zinc Alloy Die-Cast, Black-finished	
Lens	plastic, Acrylic	
Electrical connection	Cable, 2 m, PVC	
Number of cores	4	
Core cross-section	0.34 mm²	
Ambient temperature	-10+50 °C	
Relative humidity	090%	
Protection class	IP67	
Special features	keep/defer	
Power-on indication	LED, Green	
Switching state	LED, Yellow	

Wiring Diagram



Functional principle

The color mark sensor differentiates between all conventional color contrasts occuring in product and material registration. For this purpose it uses green light. The very short response time of 50 μs is ideally suited for high speed applications. The sensor's switchpoint is adjusted in 15 steps via potentiometer. Via rotary switch, the sensor can also be taught to differentiate between ON and OFF state.



Excess gain indication



Tests/approvals	
Approvals	CE



Accessories

Type code	Ident no.		Dimension drawing
SMB55A	3053259	Mounting bracket, stainless steel, for R58A/R58E and QL56/QL51	12.7 12.7 12.7 13.7 15.7 15.2 80.8
SMB55RA	3053261	Mounting bracket, rectangular, stainless steel, for R58A/R58E and QL56/QL51	7,9 20,4 12,4 05,2 12,7 50,8 11,4 05,6
SMB55F	3053260	Mounting panel, stainless steel, for R58A/R58E and QL56/QL51	12.7 12.7 12.7 12.7 0 5.2 0 5.2 0 6.6
SMB55S	3053265	Mounting bracket, stainless steel, for R58A/R58E and QL56/QL51	33.6 3.8 7.9 28 11.4 11.4 11.4 15.5 15.5 15.5 15.5 15.5