


LED Signal Light Beacon With Integrated Button K30LMXXPPB2QP



Type	K30LMXXPPB2QP
ID	3025439

Signal and display data	
Purpose	LED indicator light
Function	Spotlight
Light type	Magenta
LED service life (L70)	50000 h
Switch Function	Momentary
Dimmable	No
Features of color 1	Magenta, Permanently on


Electrical data	
Operating voltage U_a	10...30 VDC
DC rated operating current I_a	≤ 25 mA
Max. current consumption per color	40 mA
Output function	NO contact, Potential-free
Input type	PNP
Response time typical	< 10 ms

Mechanical data	
Cascadable	No
Design	Dome, K30L
Dimensions	Ø 30 x 49.4 mm
Housing material	Plastic, PC, Black
Window material	Polycarbonate, diffuse
Electrical connection	Cable with connector, M12 × 1, 0.15 m, PVC
Number of cores	4
Ambient temperature	-40...+50 °C
Protection class	IP67

Tests/approvals	
MTTF	626 years acc. to SN 29500 (Ed. 99) 40 °C
Approvals	CE

- LED all-round visible
- Individually controllable
- Mechanical screw-in thread M22x1.5
- Protection class IP67
- Monochrome: Magenta (COL 1)
- Pushbutton closes potential-free contacts on Pin 1 (BN) and 2 (WH)
- Cable with male end M12 x 1
- Operating voltage 10...30 VDC

Wiring Diagram



Accessories

Type code	Ident no.		Dimension drawing
SMB22A	3079414	Mounting bracket, stainless steel, for K30L series	