


SM2A312FPHQD


Photoelectric Sensor – Photoelectric Sensor for Plastic Fibers



Features

- Cable, PVC, 2 m
- Protection class IP67
- Sensitivity adjusted via potentiometer
- Alignment indicator
- Operating voltage: 24...240 VAC
- Switching output, bipolar
- Light/dark operation

Wiring diagram




Technical data

Type	SM2A312FPHQD
ID	3034998
Optical data	
Function	Fiber optic sensor
Operating mode	Plastic fiber
Fiber-optic type	plastic
Light type	Red
Wavelength	650 nm
Electrical data	
Operating voltage	24...240 VAC
Output function	Relay output
Mechanical data	
Design	Rectangular, Mini Beam
Housing material	Plastic, PBT, Yellow
Lens	plastic, Acrylic
Electrical connection	Cable
Ambient temperature	-20...+70 °C
Protection class	IP67
Tests/approvals	
Approvals	CE, cURus, CSA

Functional principle

Glass or plastic fibers are the optimum choice for high-temperature applications and limited spaces. Optical fibers transfer the light from the sensor to a remote object. Individual fibers are used for opposed sensing mode, whereas bifurcated fibers are suited for diffuse sensing mode.


Excess gain curve
Excess gain in relation to distance



Accessories

SMB18A


3033200



Mounting bracket, rectangular, stainless steel, for sensors with 18 mm thread

SMB18AFAM10


3012558



Mounting bracket, material VA 1.4401, for M10 x 1.5 thread, thread length 18 mm

SMB18SF


3052519



Mounting bracket, PBT black, for sensors with 18 mm thread, rotatable

SMB312B


3025519



Mounting bracket, stainless steel, for MINI-BEAM NAMUR

SMB3018SC

3053952



Mounting bracket, PTB black, for sensors with 18 mm thread