


Photoelectric Sensor Touch Switch For Two-Hand Control System STBVP6LQ5





Туре	STBVP6LQ5
ID	3064184


Optical data	
Function	Touch Button
Light type	IR
Electrical data	
Operating voltage U _B	1030 VDC
DC rated operating current I _e	≤ 75 mA
Output function	NO/NC, PNP
Switching frequency	≤ 25 Hz

Mechanical data	
Design	Rectangular, STB
Housing material	Plastic, PBT
Electrical connection	Connector, M12 × 1
Ambient temperature	0+50 °C
Protection class	IP66
Power-on indication	LED, Green
Switching state	LED, Green
Error indication	LED, green, Flashing

Tests/approvals

- M12 × 1 male, 4-pin
- Protection class IP66
- Ergonomically shaped
- Upper housing part of Lexan
- Operating voltage: 10...30 VDC
- 1 safety NO output PNP
- 1 safety NC output PNP
- Pre-assembled protective cover
- Safety category 4 according to EN ISO 13849-1 for use with corresponding evaluation relays
- SIL 3 acc. to IEC 61508 and IEC 62061

Wiring Diagram



Functional principle

The Duo-Touch two-hand control system can be used as a triggering device for most motor driven machines whose machining cycle is controlled by an operator. If a two-hand control system is used as a protective device, both of the operators hands must be used to start the machine cycle. The operator is thus placed in a form of "protective custody" if a hazard exists from which the operator must be protected or must avoid. The control elements of the two-hand control system must be arranged so that the hazardous motion (e.g. closing of a punching press) is completed or stopped before the operator can release one



or both keys and reach the hazard area. Both hands must be used simultaneously. Both keys must be pressed within a time of max. 500 ms (simultaneity requirement according to EN 574).