


LED Signal Light Beacon K50BCLS1XWXP



Type	K50BCLS1XWXP
ID	3085095

Signal and display data	
Purpose	LED indicator light
Function	Spotlight
Light type	White
LED service life (L70)	50000 h
Dimmable	No
Features of color 1	White, Miscellaneous
Special features	Wash down


Electrical data	
Operating voltage U_o	12...30 VDC
DC rated operating current I_o	≤ 160 mA
Max. current consumption per color	160 mA
Input type	PNP
Response time typical	< 0.25 ms

Mechanical data	
Cascadable	No
Design	Puck, K50BL
Dimensions	Ø 50 x 49 mm
Housing material	Plastic, PC, Black
Window material	Polycarbonate, clear
Electrical connection	Cable, 2 m, PVC
Number of cores	5
Ambient temperature	-40...+50 °C
Relative humidity	0...90%
Protection class	IP67 IP69

Tests/approvals	
Approvals	CE, cULus listed

- Flashing LED
- Top and side view
- Two flashing speeds
- Screw-in thread M30x1.5
- Protection class IP67
- Monochrome: White flashing (COL 2)
- Cable 2 m
- Operating voltage 12...30 VDC

Wiring Diagram



Functional principle

The LED is IP67/ IP69k rated and suited for indoor and outdoor applications. The rotating and blinking K50 Beacon produces a very bright and all-round visible signal

Accessories

Type code	Ident no.		Dimension drawing
SMB30A	3032723	Mounting bracket, rectangular, stainless steel, for sensors with 30mm thread	
SMB30SC	3052521	Mounting bracket, PBT black, for sensors with 30 mm thread, rotatable	