




Pick-to-Light Placement Sensor Capacitive Button K50ABTRXHQ



Type	K50ABTRXHQ
ID	3093108
Signal and display data	
Purpose	Pick-to-Light
Function	Touch Button
Light type	Red
LED service life (L70)	50000 h
Switch Function	Momentary
Electrical data	
Operating voltage U_o	12...30 VDC
DC rated operating current I_o	≤ 150 mA
Output function	NO contact, PNP/NPN
Mechanical data	
Design	Cylinder, threaded, K50
Dimensions	Ø 50 x 66 mm
Housing material	Plastic, PC
Window material	Plastic, diffuse
Electrical connection	Connector, M12 × 1
Ambient temperature	-40...+50 °C
Protection class	IP67 IP69
Tests/approvals	
MTTF	146 years acc. to SN 29500 (Ed. 99) 40 °C
Approvals	CE, UL listed

- Protection classes IP67 / IP69K
- Male M12 x 1, 5-pin
- Disabled: Red (COL 1)
- Enabled: No color
- Operating voltage 10...30 VDC
- Bipolar circuit
- NO contact

Wiring Diagram




Functional principle

The K50 placement sensor is suitable for many mounting and component placement applications. LED light is reflected perfectly by the entire dome. The device has two display colors depending on the version: Color 1 Shows the disabled state, color 2 the enabled

state. Since the device has no inputs, a color change is exclusively realized by touching the sensor (enable). Devices with a hold function keep the enabled state, even when the contact ends.

Accessories

Type code	Ident no.		Dimension drawing
SMB30A	3032723	Mounting bracket, rectangular, stainless steel, for sensors with 30mm thread	
SMB30SC	3052521	Mounting bracket, PBT black, for sensors with 30 mm thread, rotatable	
SMB30FA	3074005	Montagewinkel; Werkstoff VA 1.4401	

