


WL50SWSSGL5PWMQ

LED Spotlight – In the Metal Housing




Technical data

Type	WL50SWSSGL5PWMQ
ID	3093188
Signal and display data	
Purpose	LED work light
Function	Spotlight
Light type	White
Color temperature	5000...+8300 K
Luminous flux lumen	295 lm
Aperture angle degree	5 °
Beam angle	5°
LED service life (L70)	50000 h
Dimmable	PWM
Features of color 1	White, Permanently on, 295 lm
Special features	Chemical-resistant Wash down Resistant to chemicals
Electrical data	
Operating voltage U _B	12...30 VDC
DC rated operating current I _o	≤ 400 mA
Input power	1.7 W
Mechanical data	
Cascadable	No
Design	Puck, WL50S
Dimensions	Ø 56 x 71.1 mm
Housing material	Metal, Stainless steel
Window material	Glass, clear
Electrical connection	Connector, M12 × 1, PVC

Features

- Operating voltage: 12...30 VDC
- Protection class: IP69K
- Stainless steel housing
- Color: White
- M12 x 1 male, straight, 4-pin
- Dimmable via PWM input

Wiring diagram




Functional principle

The energy-efficient LED work lights are ideally suited for industrial applications. The rugged IP69K protected versions can be used in many demanding applications where bright and uniform illumination is required. The electrical connection is either established via standard M12x1 connector or pigtail directly at the clamp connection of existing installations. On some models the light output is continuously dimmable via a PWM signal on pin 4.

Technical data

Number of cores	5
Ambient temperature	-20...+50 °C
Storage temperature	-40...+70 °C
Relative humidity	0...95 %
Protection class	IP67 IP69
Tests/approvals	
Approvals	CE

Accessories

Dimension drawing	Type	ID	
	RKC4.4T-2/TEL	6625013	Connection cable, M12 female connector, straight, 4-pin, cable length: 2 m, jacket material: PVC, black; cULus approval
	WKC4.4T-2/TEL	6625025	Connection cable, M12 female connector, angled, 4-pin, cable length: 2 m, jacket material: PVC, black; cULus approval