

WLB92ZC550ACT

LED Linear Light – In the Metal Housing

Technical data

Type	WLB92ZC550ACT
ID	3093277
Signal and display data	
Purpose	LED work light
Function	Linear light
Light type	White
Color temperature	4700...+5300 K
Luminous flux lumen	3130 lm
Dimmable	Voltage input
Features of color 1	White, Permanently on, 3510 lm
Electrical data	
Operating voltage U _B	100...277 VAC
Mechanical data	
Cascadable	Yes
Design	Rectangular, WLB92
Dimensions	651 x 97 x 104 mm
Housing material	Metal, AL, Anodized
Window material	Polycarbonate, diffuse
Electrical connection	Cable entry
Number of cores	5
Ambient temperature	-35...+50 °C
Protection class	IP40
Tests/approvals	
Approvals	CE




Features

- Light beam: 550 mm
- Operating voltage: 110...277 VAC
- Protection class: IP40
- Color: White
- ½" cable entry
- Stepless dimming of light output (0% - 100%) with analog dimmer (0...10 VDC), not incl. in delivery

Accessories


LMBWLB92	3093567
----------	---------

Snap bracket for WLB92 work light, included in the WLB92 scope of delivery



LMBWLB92CLIP	3093568
--------------	---------


Snap bracket for WLB92 linear light



LMBWLB92HK5

3093569


Pendant mounting bracket for WLB92



LMBWLB92S

3093570

Mounting bracket for front side mounting of the WLB92



LMBWLB92RAS

3093571

Pivoting mounting bracket for WLB92 line light

