


Actuator and Sensor Cable, PUR Quick-turn Connection Cable RKC5Q-10/TXL




- Female M12, straight, 4-pin + PE
- Jacket material: PUR
- Jacket color: black
- Suitable for drag chain use
- Resistant to welding sparks
- Resistant to chemicals, UV radiation and oils
- Flame-retardant
- Free from halogen, silicone, PVC and LABS
- Particularly resistant to abrasion
- RoHS-compliant
- Protection class IP67
- Cable length: 10 m

Type	RKC5Q-10/TXL
ID	6628048
Connector A	Female, M12 × 1, Straight, A-coded
Number of pins	4+PE
Contact carriers	Plastic, TPU, Black
Connector body	Plastic, TPU, Yellow
Interlocking sleeve	Plastic, PBT, black
Mechanical lifespan	> 50 Mating cycles
Pollution degree	3
Protection class	IP67, (plugged)

Cable	
Cable diameter	Ø 4.8mm ±0.20
Cable length	10 m m
Cable jacket	PUR, Black
Core insulation	PP
Core cross-section	5 x 0.34 mm²
Arrangement of strands	42 x 0.1mm
Core colors	BN, WH, BU, BK, GNYE

Electrical properties at +20 °C	
Rated voltage	60V
Test voltage	2000 V
Current	4AA
Insulation resistance	> 30.5 MΩ/km
forward resistance	max. 57 Ω/km








Circuit Diagram

1	BN
2	WH
4	BK
3	BU
5	GNYE

Mechanical and chemical properties	
Bending radius (stationary installation)	$\geq 5 \times \varnothing$
Bending radius (flexible use)	$\geq 10 \times \varnothing$
Bending cycles	≥ 5 million
Admissible acceleration	max. 5 m/s ²
Admissible travel path, horizontal	5 m (at 5 m/s ²)
Admissible travel path, vertical	2 m (at 5 m/s ²)
Admissible traversing speed	3.3 m/s
Torsional stress	$\pm 180^\circ/\text{m}$
Ambient temperature (fixed)	-50...+80°C
Ambient temperature (mobile)	-25...+80°C
Ambient temperature (drag chain)	-25...+60°C

Accessories

Type code	Ident no.		Dimension drawing
BS8151-0	6904611	Field-wireable male connector, M12 × 1, straight, 5-pin, screw terminal connection, cable feedthrough 4.0 to 6.0 mm, core cross-section/terminal capacity 0.14 to 0.75 mm², plastic housing, metal retaining screw	 Technical drawing of the BS8151-0 connector. It is a straight, 5-pin male connector with an M12 x 1 screw thread. The drawing shows a side view with dimensions: overall length 60.4 mm, outer diameter 20.2 mm, and pin positions 18, 14, and 13 mm from the end.
BS8251-0	6904612	Field-wireable male connector, M12 × 1, angled, 5-pin, screw terminal connection, cable feedthrough 4.0 to 6.0 mm, core cross-section/terminal capacity 0.14 to 0.75 mm², plastic housing, metal retaining screw	 Technical drawing of the BS8251-0 connector. It is an angled, 5-pin male connector with an M12 x 1 screw thread. The drawing shows a side view with dimensions: overall length 42.6 mm, outer diameter 20.2 mm, and pin positions 18 and 13 mm from the end. The angled part has a length of approximately 33 mm.
FW-ERSPM0526-SA-P-0408	100002535	Field-wireable male connector, M12 × 1, straight, 5-pin, push-in connection, cable feedthrough 4.0 to 8.0 mm, core cross-section/terminal capacity 0.14 to 0.75 mm², plastic housing, metal retaining screw	 Technical drawing of the FW-ERSPM0526-SA-P-0408 connector. It is a straight, 5-pin male connector with an M12 x 1 screw thread. The drawing shows a side view with dimensions: overall length 60.0 mm, outer diameter 20.2 mm, and pin positions 19, 15, and 15 mm from the end.
FW-ERSPM0516-SA-S-0408	100002289	Field-wireable male connector, M12 × 1, straight, 5-pin, screw terminal connection, cable feedthrough 4.0 to 8.0 mm, core cross-section/terminal capacity 0.25 to 1.5 mm², plastic housing, metal retaining screw	 Technical drawing of the FW-ERSPM0516-SA-S-0408 connector. It is a straight, 5-pin male connector with an M12 x 1 screw thread. The drawing shows a side view with dimensions: overall length 61.0 mm, outer diameter 20.2 mm, and pin positions 20, 13, 12, and 20 mm from the end.
FW-EWSPM0516-SA-S-0408	100002291	Field-wireable male connector, M12 × 1, angled, 5-pin, screw terminal connection, cable feedthrough 4.0 to 8.0 mm, core cross-section/terminal capacity 0.25 to 1.5 mm², plastic housing, metal retaining screw	 Technical drawing of the FW-EWSPM0516-SA-S-0408 connector. It is an angled, 5-pin male connector with an M12 x 1 screw thread. The drawing shows a side view with dimensions: overall length 42.0 mm, outer diameter 20.2 mm, and pin positions 20, 18, and 17 mm from the end. The angled part has a length of 20 mm.
TORQUE-WRENCH-SET-AS	6936170	Torque wrench set; handles with adjustable torque 0.4-1.0 Nm, torque wrench for M8 (SW9), fork wrench for M12 (SW 14)	

Accessories

Type code	Ident no.		Dimension drawing
BLANK-LABEL-FOR-CORDSETS-TEL-TXL	6936206	Label for TEL and TXL cables, length: 18 mm, height: 4 mm, material: polycarbonate (PC), color: white, halogen-free and flame-retardant	