


Actuator and Sensor Cable, PUR
Quick-Turn Extension Cable
WKC5Q-2-RSC5Q/TXL



- Female M12, angled, 4-pin + PE
- Male M12, straight, 4-pin + PE
- Jacket material: PUR
- Jacket color: black
- Suitable for drag chain use
- Resistant to welding sparks
- Resistant to chemicals, UV radiation and oils
- Flame-retardant
- Free from halogen, silicone, PVC and LABS
- Particularly resistant to abrasion
- RoHS-compliant
- Protection class IP67
- Cable length: 2.0 m

Type	WKC5Q-2-RSC5Q/TXL
ID	6628062
Remark to product	!!! Pin 5 = PE !!!

Connector A	Female, M12 × 1, Angled, A-coded
Number of pins	4+PE
Contact carriers	Plastic, TPU, Black
Connector body	Plastic, TPU, Yellow
Interlocking sleeve	Plastic, PBT, black
Mechanical lifespan	> 50 Mating cycles
Pollution degree	3
Protection class	IP67, (plugged)

Connector B	Male, M12 × 1, Straight, A-coded
Number of Pins	4+PE
Contact carriers	Plastic, TPU, Black
Connector body	Plastic, TPU, Yellow
Interlocking sleeve	Plastic, PBT, black
Mechanical life	> 50 Mating cycles
Pollution degree	3
Protection class	IP67, (Plugged)

Cable	
Cable diameter	Ø 4.8mm ±0.20
Cable length	2 m m
Cable jacket	PUR, Black
Core insulation	PP
Core cross-section	5 x 0.34 mm²
Arrangement of strands	42 x 0.1mm
Core colors	BN, WH, BU, BK, GNYE



Circuit Diagram




Electrical properties at +20 °C

Rated voltage	60V
Test voltage	2000 V
Current	4AA
Insulation resistance	> 30.5 MΩ/km
forward resistance	max. 57 Ω/km

Mechanical and chemical properties

Bending radius (stationary installation)	≥ 5 x Ø
Bending radius (flexible use)	≥ 10 x Ø
Bending cycles	≥ 5 million
Admissible acceleration	max. 5 m/s ²
Admissible travel path, horizontal	5 m (at 5 m/s ²)
Admissible travel path, vertical	2 m (at 5 m/s ²)
Admissible traversing speed	3.3 m/s
Torsional stress	± 180 °/m
Ambient temperature (fixed)	-50...+80°C
Ambient temperature (mobile)	-25...+80°C
Ambient temperature (drag chain)	-25...+60°C

Accessories

Type code	Ident no.		Dimension drawing
TORQUE-WRENCH-SET-AS	6936170	Torque wrench set; handles with adjustable torque 0.4-1.0 Nm, torque wrench for M8 (SW9), fork wrench for M12 (SW 14)	
BLANK-LABEL-FOR-CORDESETS-TEL-TXL	6936206	Label for TEL and TXL cables, length: 18 mm, height: 4 mm, material: polycarbonate (PC), color: white, halogen-free and flame-retardant	