


# RKS4.4T-55/TEL

## Actuator and Sensor Cable, PVC – Connection Cable



### Technical data


|                                        |                                        |
|----------------------------------------|----------------------------------------|
| Type                                   | RKS4.4T-55/TEL                         |
| ID                                     | 6635077                                |
| Connector A                            | Female, M12 × 1, Straight, A-coded     |
| Number of pins                         | 4                                      |
| Contacts                               | Brass, CuZn, Gold-plated               |
| Contact carriers                       | Plastic, TPU, Black                    |
| Connector body                         | Plastic, TPU, Black                    |
| Coupling nut/screw                     | Brass, CuZn, Nickel-plated             |
| Seal                                   | Plastic, FPM/FKM                       |
| Mechanical lifespan                    | > 100 Mating cycles                    |
| Pollution degree                       | 3                                      |
| Protection class                       | IP67, IP69K, Only in screwed condition |
| <b>Cable</b>                           |                                        |
| Cable diameter                         | Ø 5.4 mm ±0.20                         |
| Cable length                           | 55 m                                   |
| Cable jacket                           | PVC, Black                             |
| Shielding                              | Aluminum foil, tinned copper wire      |
| Core insulation                        | PVC                                    |
| Core cross-section                     | 4 x 0.34 mm <sup>2</sup>               |
| Arrangement of strands                 | 42 x 0.1 mm                            |
| Core colors                            | BN, WH, BU, BK                         |
| <b>Electrical properties at +20 °C</b> |                                        |
| Rated voltage                          | 250 V                                  |
| Test voltage                           | 2000 V                                 |
| Current                                | 4 A                                    |
| Insulation resistance                  | > 30.5 MΩ/km                           |
| forward resistance                     | max. 57 Ω/km                           |

### Features




- Female M12, straight, 4-pin
- Shield on coupling nut/screw
- Jacket material: PVC, shielded
- Jacket color: black
- Resistant to chemicals and oils
- Flame retardant
- Resistant to acids and alkaline solutions
- Resistant to microbes and hydrolysis
- LABS free
- Protection class: IP67, IP69K

### Cable Cross-Section




### Contact assignment



Technical data

| Mechanical and chemical properties       |               |
|------------------------------------------|---------------|
| Bending radius (stationary installation) | ≥ 5 x Ø       |
| Bending radius (flexible use)            | ≥ 10 x Ø      |
| Ambient temperature (fixed)              | -40...+105 °C |
| Ambient temperature (mobile)             | 0...+80 °C    |
| Approvals                                | cULus         |

Circuit Diagram



Accessories

|                                                                                                                       |         |                                                                                                                                         |         |
|-----------------------------------------------------------------------------------------------------------------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------|---------|
| TORQUE-WRENCH-SET-AS                                                                                                  | 6936170 | BLANK-LABEL-FOR-CORDSETS-TEL-TXL                                                                                                        | 6936206 |
| Torque wrench set; handles with adjustable torque 0.4-1.0 Nm, torque wrench for M8 (SW9), fork wrench for M12 (SW 14) |         | Label for TEL and TXL cables, length: 18 mm, height: 4 mm, material: polycarbonate (PC), color: white, halogen-free and flame-retardant |         |



Accessories

| Dimension drawing | Type                  | ID        |                                                                                                                                                                            |
|-------------------|-----------------------|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                   | LABEL-HOLDER-FLEX-PVC | 100048170 | PVC label holder for identification of extension cables (TEL/TXL product series); for cable diameters: min. 5 mm; dimensions 4 × 18 mm; delivery unit: 50 pcs. per package |