


CMBSD8181-0

Field-Wireable Connector


Male Connector M12 × 1, Straight



Features

- A-coding
- Metal housing
- Shieldable
- Screw-clamp terminal
- 8-pin
- Cable feedthrough 6...8 mm
- Core cross-section 0.14...0.50 mm²

Contact assignment



Technical data

Type	CMBSD8181-0
ID	6936290
Connector A	Male, M12 × 1, Straight
Number of pins	8
Contacts	CuZn, Gold-plated
Contact carriers	Plastic, PA, Black
Connector body	Die-cast Zinc, GD-Zn, nickel-plated, Black
Coupling nut/screw	Die-cast Zinc, GD-Zn, Nickel-plated
Seal	Plastic, FPM/FKM
External diameter of the cable	4...8 mm
Core cross-section/Clamping ability	0.14...0.5 mm ²
Connection mode	Screw/clamp connection
Mechanical lifespan	> 100 Mating cycles
Protection class	IP67, (screwed together)
Network protocol	Ethernet
Electrical properties at +20 °C	
Rated voltage	30 V
Current	2 A
Insulation resistance	≥ 10 ⁹ Ω
Mechanical and chemical properties	
Ambient temperature (fixed)	-40...+85 °C
Note	
- We reserve the right to make technical modifications without prior notice.	